
	DECLARATION OF PERFORMANCE	
		Σελ. 1 από 1
No 03.01		

1. Unique identification code of the product-type:

Strong Bond Grey, GP CS IV

Intended use:

**General purpose (GP) rendering mortar for use
on external walls, ceilings and columns**

2. Manufacturer:

**Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area,
GR-19300 Aspropyrgos, Greece**

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

System 4 & System 4 for Reaction to Fire

4. Harmonised Standard: **EN 998-1:2016**

Notified Bodies:

Center for Testing and European Certification LTD (CTEC), NB 1871

5. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	Euroclass A1
Water Absorption	W _c 2
Water Vapour Permeability (μ)	15/35
Adhesion	0.6 (FP B)
Thermal Conductivity (λ)	0.82 W/m·K (Tab. Value, P=50%)
Durability	NPD
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



Sokratis Vavatsikos

Chemist N.K.U.A. | Product Safety

Aspropyrgos-Greece, on 24/09/2021