

	DECLARATION OF PERFORMANCE	CE
		Σελ. 1 από 1
No 03.21		

1. Unique identification code of the product-type:

ClimaTop® FlexoSil (Fine, K8, K10, K15, R15, K20)

Intended use:

**External renders based on organic binders for use
on external walls, ceilings and columns**

2. Manufacturer:

**Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area,
GR-19300 Aspropyrgos, Greece**

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

System 4 & System 3 for Reaction to Fire

4. Harmonised Standard: **EN 15824:2017**

5. Notified Bodies:

Center for Testing and European Certification LTD (CTEC), NB 1871

6. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	A2-s1,d0
Water Vapour Permeability	V ₂
Water Absorption	W ₁
Adhesion	0.3 MPa
Durability	NPA*
Thermal Conductivity (λ)	1.30 W/m·K
Dangerous substances	See SDS

*NPA: No Performance Assessed

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



Sokratis Vavatsikos

Chemist N.K.U.A. | Product Safety

Aspropyrgos-GREECE, on 27/08/2021