

	<b>DECLARATION OF PERFORMANCE</b>	<b>CE</b>
		Page 1 of 1
<b>No 03.22</b>		

1. Unique identification code of the product-type:

**ClimaTop® Classic (K8, K10, K12, K15, R15, K20)**

Intended use:

**External renders based on organic binders for use  
on external walls, ceilings and columns**

2. Manufacturer:

**Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area,  
GR-19300 Aspropyrgos, Greece**

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

**System 4 & System 3 for Reaction to Fire**

4. Harmonised Standard: **EN 15824:2017**

5. Notified Bodies:

**Center for Testing and European Certification LTD (CTEC), NB 1871**

6. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	A2-s1,d0
Water Vapour Permeability	V <sub>2</sub>
Water Absorption	W <sub>1</sub>
Adhesion	≥ 0.3 MPa
Durability	≥ 0.3 MPa
Thermal Conductivity (λ)	1.30 W/m·K
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



**Sokratis Vavatsikos**

Chemist N.K.U.A. | Product Safety

Aspropyrgos-GREECE, on 10/02/2023